PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-244237

(43) Date of publication of application: 19.09.1997

(51)Int.CI.

G03F 7/004

B41C 1/055

B41N 1/14

G03F 7/075

(21)Application number : 08-052737

(71)Applicant: TOYO INK MFG CO LTD

(22)Date of filing:

11.03.1996

(72)Inventor: TANAKA YASUHIRO

TOBA YASUMASA

(54) COMPOSITION CAPABLE OF INCREASING SURFACE ENERGY AND PRINTING PLATE MATERIAL USING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To unnecessitate a developing process after an imagewise exposing process and to obtain a printing plate using no dampening water at the time of printing by using a solid organopolysiloxane compd. and a photothermic conversion material dispersed in the compd. SOLUTION: This compsn. is composed of an organopolysiloxane compd. and a photothermic conversion material dispersed in the compd. The compd. is, e.g. dimethylpolysiloxane, methylhydrogenpolysiloxane, methylpolysiloxane having hydrogen atoms at both terminals. methylphenylpolysiloxane, alkyl modified polysiloxane, amino modified polysiloxane or carboxyl modified polysiloxane. A coloring material effectively absorbing light in a wavelength region from UV to near IR and capable of efficiently converting the light into heat energy is preferably used as the photothermic conversion material.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office